


Stile & Rail Doors

Positive Pressure, Neutral Pressure, Environmental

Standard Models: WSR

 Environmental Models: EWSR, EWSRUF

Product Features and Specifications	20 Minute PP – Interior Only	90 Minute PP or NP – Interior Only
Thickness	1-3/4", 2", 2-1/4"	Same
Maximum Size	Single: 3/6 x 8/0 Pair: 7/0 x 8/0	Same
Minimum Size	1/2 x 1/4	1/4 x 1/4
Faces:	Wood Veneer	Same
Stile Edge	Matching Wood	Same
Sticking & Stops	Matching Wood	Same
Core Material	Panels - MDF	Composite
Adhesives	Stiles & Rails: Particleboard or MDF	
Joinery	Type 1 (waterproof)	Same
Panel Construction	Tongue & groove plus dowels	Doweled
Raised 1 side	N/A	N/A
Raised 2 sides	1-1/4"	Single - 1-15/32" Pair - 1-11/16"
Flat	5/8"	Single - 15/16" Pair - 1-11/32"
Step	1-1/4"	N/A
Step Rim	1-1/4"	N/A
Panel Size	Minimum: 6" x 6" Maximum: 32" x 85"	Minimum: 6-6" Maximum: 32" x 85"
Stock Dimensions		
Top Rail	5"	5"
Center Rails	3-5/8"	3 5/8"
Lock Rail	7-3/4"	7-3/4"
Bottom Rail	8-1/2"	8-1/4"
Mullions	3-5/8"	3-5/8"
Muntins	N/A	N/A
Stiles	5-1/16"	5-1/16"
Bottom of door to:		
top of lock rail	39" or specify	Same
Lite Opening	Factory glazed: FireLite® Plus or NT, 1,040sq in max, max width 26", max height 40"	Same
Other Detail Work	• Fitting • Machining	Same
Factory Finish	• Clear • Stain	Same
	• Prime • Paint	
Warranty	Limited Life: original installation	Same
Acoustic Rating	N/A	39 (Operable)
Environmental Options & LEED Credit Contributions	<ul style="list-style-type: none"> • MR 4 - Recycled Content — all models • MR 7 - Certified Wood — contact Sales Center • IEQ 4.4 - Low-Emitting Materials — all UF models No Added Urea Formaldehyde Resins	<ul style="list-style-type: none"> • MR 4 - Recycled Content — all models • MR 7 - Certified Wood — contact Sales Center • IEQ 4.4 - Low-Emitting Materials — all UF models No Added Urea Formaldehyde Resins



Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.